

```

<?xml version="1.0" encoding="UTF-8"?>
<project xmlns="http://maven.apache.org/POM/4.0.0"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://maven.apache.org/POM/4.0.0
http://maven.apache.org/maven-v4_0_0.xsd">

  <!-- POM file generated with GWT webAppCreator -->
  <modelVersion>4.0.0</modelVersion>
  <groupId>com.mypact.poc</groupId>
  <artifactId>docver</artifactId>
  <packaging>war</packaging>
  <version>1.0-SNAPSHOT</version>
  <name>GWT Maven Archetype</name>

  <properties>
    <!-- Convenience property to set the GWT version -->
    <gwtVersion>2.1.0</gwtVersion>
    <!-- GWT needs at least java 1.5 -->
    <maven.compiler.source>1.5</maven.compiler.source>
    <maven.compiler.target>1.5</maven.compiler.target>
    <webappDirectory>${project.build.directory}/$
{project.build.finalName}</webappDirectory>
  </properties>

  <dependencies>
    <dependency>
      <groupId>com.google.gwt</groupId>
      <artifactId>gwt-servlet</artifactId>
      <version>2.2.0</version>
      <scope>runtime</scope>
    </dependency>
    <dependency>
      <groupId>com.google.gwt</groupId>
      <artifactId>gwt-user</artifactId>
      <version>2.2.0</version>
      <scope>provided</scope>
    </dependency>
    <dependency>
      <groupId>junit</groupId>
      <artifactId>junit</artifactId>
      <version>4.7</version>
      <scope>test</scope>
    </dependency>
  </dependencies>

  <build>
    <!-- Generate compiled stuff in the folder used for developing mode -->
    <outputDirectory>${webappDirectory}/WEB-INF/classes</outputDirectory>

    <plugins>

      <!-- GWT Maven Plugin -->
      <plugin>
        <groupId>org.codehaus.mojo</groupId>
        <artifactId>gwt-maven-plugin</artifactId>
        <version>2.2.0</version>
        <executions>
          <execution>
            <goals>
              <goal>compile</goal>
              <goal>test</goal>
              <goal>il8n</goal>
            </goals>
          </execution>
        </executions>
      </plugin>
    </plugins>
  </build>
</project>

```

```

        <goal>generateAsync</goal>
      </goals>
    </execution>
  </executions>
  <!-- Plugin configuration. There are many available options, see gwt-
maven-plugin
documentation at codehaus.org -->
  <configuration>
    <runTarget>docversion.html</runTarget>
    <hostedWebapp>${webappDirectory}</hostedWebapp>
    <i18nMessagesBundle>com.mypact.poc.client.Messages</i18nMessagesBundle
>
    </configuration>
  </plugin>

  <!-- Copy static web files before executing gwt:run -->
  <plugin>
    <groupId>org.apache.maven.plugins</groupId>
    <artifactId>maven-war-plugin</artifactId>
    <version>2.1.1</version>
    <executions>
      <execution>
        <phase>compile</phase>
        <goals>
          <goal>exploded</goal>
        </goals>
      </execution>
    </executions>
    <configuration>
      <webappDirectory>${webappDirectory}</webappDirectory>
    </configuration>
  </plugin>

</plugins>
</build>

</project>

```